



VARMFÖRZINKAT STÅL

Maskstorlek (c/c mm)	Tråd (mm)	Format (mm)	Material	Vikt kg/rulle
6,3 x 6,3	0,65	1000 x 25,0 Meter	Vfz	27,50
10,6 x 10,6	0,95	1000 x 25,0 Meter	Vfz	27,50
12,7 x 12,7	1,05	1000 x 25,0 Meter	Vfz	25,00
12,7 x 12,7	1,05	1220 x 25,0 Meter	Vfz	30,50
12,7 x 12,7	1,60	1000 x 25,0 Meter	Vfz	68,00
12,7 x 25,4	1,45	1000 x 25,0 Meter	Vfz	42,50
19,1 x 19,1	1,05	1000 x 25,0 Meter	Vfz	18,00
19,1 x 19,1	1,05	500 x 25,0 Meter	Vfz	9,00
19,1 x 19,1	1,05	250 x 25,0 Meeter	Vfz	4,50
25,4 x 25,4	1,75	1000 x 25,0 Meter	Vfz	42,50
25,4 x 25,4	2,05	1000 x 25,0 Meter	Vfz	50,00
50,8 x 50,8	2,05	1000 x 25,0 Meter	Vfz	27,50



ROSTFRITT STÅL

Maskstorlek (c/c mm)	Tråd (mm)	Format (mm)	Material	Vikt kg/rulle
6,3 x 6,3	0,80	1000 x 25,0 Meter	1,4301	27,50
8,5 x 8,5	1,00	1000 x 25,0 Meter	1,4301	30,00
10,0 x 10,0	1,00	1000 x 25,0 Meter	1,4301	26,00
10,0 x 10,0	1,00	1000 x 25,0 Meter	1,4404	26,00
12,7 x 12,7	1,00	1000 x 25,0 Meter	1,4301	25,00
12,7 x 12,7	1,00	1000 x 25,0 Meter	1,4404	25,00
19,1 x 19,1	1,00	1000 x 25,0 Meter	1,4301	20,00
19,1 x 19,1	1,60	1000 x 25,0 Meter	1,4301	40,00
20,0 x 20,0	1,50	1000 x 25,0 Meter	1,4301	36,00
25,4 x 25,4	2,00	1000 x 25,0 Meter	1,4301	50,00
50,8 x 50,8	2,00	1000 x 25,0 Meter	1,4301	27,50

GOLVNÄT LAGERFORMAT



ANVÄNDS SOM ARMERING TILL TUNNA PÅGJUTNINGAR OCH AVJÄMNINGSMASSOR PÅ GOLV.

Maskstorlek (c/c mm)	Tråd (mm)	Format (mm)	Material	Vikt kg/st	Antal /pall
75 x 75	2,5	1200 x 800	Stål	1,00	200 st
100 x 50	3,0	1200 x 800	Stål	1,70	200 st
100 x 50	3,0	1250 x 1250	Stål	2,50	200 st
100 x 50	3,0	2400 x 1250	Stål	4,90	200 st